

Dimmable LED MR16



Ordering Information

Model No.	Item name	Lumens ² (lm)	Watts (w)	CCT ¹ (k)	Efficacy (lm/w)	CRI	Lifetime ³ (h)	Beam Angle	Base type	Voltage (v)	Cerification	Equivalent ⁴ (w)
L6-MR16GU5.3D-7W	MR16	500	7	5000	71	80	25000	25°/40°	GU5.3	12	UL CUL FCC	50

3 YEARS WARRANTY



1. CCT Range complies to ANSI C78.377-2008.

2. Thermally stable typical lumens ($\pm 10\%$)

3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.

4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

5. Energy Star® will be available in Q1-2014.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.

Note: All lamps meet Energy Star® Integral LED Lamp requirements, and has been submitted for testing.

Dimensions

Model	MOL	Diameter
MR16	1.96"	1.97"

Note: Lamp shape conforms to ANSI C78.21-2003.

Note: Designed to comply with RoHS Directive 2002/95/EC.

Energy Savings

Model No.	Equivalent	Energy Savings
L6-MR16GU5.3D-7W	50W Incandescent	\$118

*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh. Does not include maintenance and replacement lamp savings.